

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
17 June 2004 (17.06.2004)

PCT

(10) International Publication Number
WO 2004/051239 A1

(51) International Patent Classification⁷: **G01N 19/02**

(21) International Application Number:
PCT/NL2003/000639

(22) International Filing Date:
16 September 2003 (16.09.2003)

(25) Filing Language: **Dutch**

(26) Publication Language: **English**

(30) Priority Data:
1021957 20 November 2002 (20.11.2002) **NL**

(71) Applicant (*for all designated States except US*): **TEN CATE THIOLON B.V. [NL/NL]; G. Van der Muelenweg 2, NL-7443 RE Nijverdal (NL).**

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **MARINUS, Hendrikus, Olde, Weghuis [NL/NL]; Enschedesestraat 119, NL-7574 AB Oldenzaal (NL). GERBEN, Christiaan,**

Bierma [NL/NL]; Diekmanstraat 22, NL-7541 WS Enschede (NL). **HAZENBERG, Hendrik** [NL/NL]; Haaksbergerstraat 174-606, NL-7413 EB Enschede (NL). **WITBREUK, Ingo, Wynand** [NL/NL]; Duivekervel 21, NL-7577 CK Oldenzaal (NL).


(74) Agents: **VALKONET, Rutger, Jr, et al.; Algemeen Octrooi-en Merkenbureau, P.O. Box 645, NL-5600 AP Eindhoven (NL).**

(81) Designated States (*national*): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.**

(84) Designated States (*regional*): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,**

[Continued on next page]

(54) Title: DEVICE FOR MEASURING THE STATIC AND/OR DYNAMIC FRICTION COEFFICIENT OF A SURFACE



(57) Abstract: The present invention relates to a device for measuring the static and/or dynamic friction coefficient of a surface, in particular a natural or artificial grass surface, which device comprises a housing placed on supports, which is to be positioned on the surface to be examined; a rotatable shaft, which is vertically disposed in said housing; a body connected to the end of said shaft that faces towards the surface, which body comprises a contact surface which can be brought into contact with the surface to be examined; as well as measuring means for measuring, during operation, the torque caused by the friction between the surface to be examined and the contact surface of the rotating body. The object of the present invention is to provide a device for measuring the static and/or dynamic friction coefficient of a surface which provides a more reliable and reproducible measuring result and which is furthermore user-friendly and easy to transport. According to the invention, the device is to that end

characterized in that the contact surface of the body is in line with the axis of rotation of the rotatable shaft.

WO 2004/051239 A1

BEST AVAILABLE COPY



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*